





Product

Name	20W LED embedded downlight
Reference	209040K54
Color	Sand white/sand silver reflective cup
RAL	As per request
Category	downlight

Light Source

Type	LED
Gross luminous flux	2800 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	20W
Current	350 mA
Efficacy	120 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	20W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP54
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	(Installation opening: ø125mm) ø158xh106
Weight	
Units per package	1
Materials	Die cast aluminum+PC lens
Diffuser	





Product

Name	30W LED surface mounted downlight
Reference	328040K54
Color	White/Black
RAL	As per request
Category	downlight

Light Source

Type	LED
Gross luminous flux	3000 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	30W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	Astigmatismº

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	30W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP40
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø230*H105mm
Weight	
Units per package	1
Materials	Aluminum+Milk white diffusion plate
Diffuser	





Product

Name	32W LED Three proof Bracket
Reference	328040K65
Color	Milk white
RAL	As per request
Category	

Light Source

Type	LED
Gross luminous flux	4100lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	32W
Current	350 mA
Efficacy	140 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	32W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1150*W76*H76mm
Weight	
Units per package	1
Materials	ABS+PC
Diffuser	





Product

Name	32W LED Three proof Bracket
Reference	328040K65
Color	Milk white
RAL	As per request
Category	

Light Source

Type	LED
Gross luminous flux	4100lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	32W
Current	350 mA
Efficacy	140 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	32W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1150*W76*H76mm
Weight	
Units per package	1
Materials	ABS+PC
Diffuser	





Product

Name	38W LED embedded flat panel light
Reference	388040K
Color	White
RAL	As per request
Category	panel light

Light Source

Type	LED
Gross luminous flux	4950 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	38W
Current	350 mA
Efficacy	130 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	38W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L595*W595mm
Weight	
Units per package	1
Materials	Aluminum+steel+milky white diffusion board
Diffuser	





Product

Name	22W LED embedded flat panel light
Reference	228040K20
Color	muted white
RAL	As per request
Category	panel light

Light Source

Type	LED
Gross luminous flux	1760 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	22W
Current	350 mA
Efficacy	80 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	22W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II


OTHER DATA

Sealing	IP20
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1200*W200*H50mm
Weight	
Units per package	1
Materials	Steel+Milk White PC
Diffuser	





DIMENSIONS



Product

Name	8W LED wall light
Reference	89040K65
Color	Sand black/Sand Silver
RAL	As per request
Category	wall light

Light Source

Type	LED
Gross luminous flux	800 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	8W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/36°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	8W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	
Weight	
Units per package	1
Materials	Aluminum+transparent tempered glass
Diffuser	





Product

Name	30W LED embedded downlight
Reference	308040K54
Color	Sand white/sand silver reflective cup
RAL	As per request
Category	downlight

Light Source

Type	LED
Gross luminous flux	3000 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	30W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/45°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	30W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP54
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø135*H65mm (Opening: Ø115mm)
Weight	
Units per package	1
Materials	Die cast aluminum+PC lens
Diffuser	





Product

Name	32W LED Three proof Bracket
Reference	328040K65
Color	Milk white
RAL	As per request
Category	

Light Source

Type	LED
Gross luminous flux	2880 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	32W
Current	350 mA
Efficacy	90 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	32W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1150*W76*H76mm
Weight	
Units per package	1
Materials	ABS+PC
Diffuser	





Product

Name	22W LED Surface mounted flat panel lamp
Reference	228040K20
Color	muted white
RAL	As per request
Category	panel light

Light Source

Type	LED
Gross luminous flux	3000 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	22W
Current	350 mA
Efficacy	140 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	Astigmatism°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	22W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP44
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1200*W200*H69mm
Weight	
Units per package	1
Materials	Steel+Milk White PC
Diffuser	





Product

Name	22W LED Surface mounted flat panel lamp
Reference	228040K20
Color	muted white
RAL	As per request
Category	panel light

Light Source

Type	LED
Gross luminous flux	3000 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	22W
Current	350 mA
Efficacy	140 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	Astigmatism°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	22W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP44
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1200*W200*H69mm
Weight	
Units per package	1
Materials	Steel+Milk White PC
Diffuser	

