





Product

Name	18W LED linear buried light
Reference	188030K67
Color	Brushed stainless steel
RAL	As per request
Category	Linear light

Light Source

Type	LED
Gross luminous flux	1600 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	18W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	30°/45°/60°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	18W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP67
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L560*W55*H76mm
Weight	
Units per package	1
Materials	stainless steel+Aluminum+transparent tempered glass
Diffuser	





Product

Name	12W LED underwater buried light
Reference	128030K68
Color	Brushed stainless steel
RAL	As per request
Category	Underwater light

Light Source

Type	LED
Gross luminous flux	1200 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	12W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/38°/55°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	12W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP68
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø100*H85mm
Weight	
Units per package	1
Materials	stainless steel+Aluminum+transparent tempered glass
Diffuser	





Product

Name	10W/m LED waterproof light strip
Reference	108030K67
Color	
RAL	As per request
Category	Strip light

Light Source

Type	LED
Gross luminous flux	960 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	10W
Current	350 mA
Efficacy	96 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	10W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP67
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	W10mm
Weight	
Units per package	1
Materials	
Diffuser	





Product

Name	10W LED linear frameless buried light
Reference	108030K68
Color	Aluminum oxide color
RAL	As per request
Category	Linear light

Light Source

Type	LED
Gross luminous flux	600 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	10W
Current	350 mA
Efficacy	60 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	Astigmatism

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	10W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP68
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L620*W32*H45mm
Weight	
Units per package	1
Materials	Aluminum+internally sandblasted acrylic
Diffuser	





Product

Name	36W LED linear buried light
Reference	368030K67
Color	Brushed stainless steel
RAL	As per request
Category	Linear light

Light Source

Type	LED
Gross luminous flux	3200 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	36W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	30°/45°/60°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	36W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP67
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1000*W55*H76mm
Weight	
Units per package	1
Materials	stainless steel+Aluminum+transparent tempered glass
Diffuser	





Product

Name	34W LED linear frameless buried light
Reference	348030K68
Color	Aluminum oxide color
RAL	As per request
Category	Linear light

Light Source

Type	LED
Gross luminous flux	3400 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	34W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	Astigmatism

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	34W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP68
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1200*W32*H45mm
Weight	
Units per package	1
Materials	Aluminum+internally sandblasted acrylic
Diffuser	





Product

Name	28W LED surface mounted downlight
Reference	289030K65
Color	Grey RAL 9006
RAL	As per request
Category	downlight

Light Source

Type	LED
Gross luminous flux	2700 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	28W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/36° /60°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	28W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø170*H160mm
Weight	
Units per package	1
Materials	Die cast aluminum+Transparent tempered glass
Diffuser	





Product

Name	20W LED linear frameless buried light
Reference	208030K68
Color	Aluminum oxide color
RAL	As per request
Category	Linear light

Light Source

Type	LED
Gross luminous flux	1200 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	20W
Current	350 mA
Efficacy	60 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	Astigmatism

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	20W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP68
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L1200*W32*H45mm
Weight	
Units per package	1
Materials	Aluminum+internally sandblasted acrylic
Diffuser	





Product

Name	18W LED linear frameless buried light
Reference	108030K68
Color	Aluminum oxide color
RAL	As per request
Category	Linear light

Light Source

Type	LED
Gross luminous flux	1800 lm
Color temperature	3000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	18W
Current	350 mA
Efficacy	60 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	Astigmatism

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	18W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP68
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	L620*W32*H45mm
Weight	
Units per package	1
Materials	Aluminum+internally sandblasted acrylic
Diffuser	

