





Product

Name	30W LED Courtyard Light
Reference	308040K65
Color	Sand Black/Sand Silver
RAL	As per request
Category	Pillar light

Light Source

Type	LED
Gross luminous flux	3000 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	30W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	45°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	30W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	W240*D120*H3500mm
Weight	
Units per package	1
Materials	Aluminum+PC lens
Diffuser	





Product

Name	18W LED surface mounted wall light
Reference	248040K65
Color	Sand white
RAL	As per request
Category	wall light

Light Source

Type	LED
Gross luminous flux	1800 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	18W
Current	350 mA
Efficacy	100lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	18W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø275xH86mm
Weight	
Units per package	1
Materials	Die cast aluminum+Milk white PC
Diffuser	





Product

Name	12W LED surface mounted wall light
Reference	128040K65
Color	Sand white
RAL	As per request
Category	wall light

Light Source

Type	LED
Gross luminous flux	1200 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	18W
Current	350 mA
Efficacy	90lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	120°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	18W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø275xH86mm
Weight	
Units per package	1
Materials	Die cast aluminum+Milk white PC
Diffuser	





Product

Name	12W LED underwater buried light
Reference	128040K68
Color	Brushed stainless steel
RAL	As per request
Category	Underwater light

Light Source

Type	LED
Gross luminous flux	1200 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	12W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/38°/55°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	12W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II


OTHER DATA

Sealing	IP68
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø100*H85mm
Weight	
Units per package	1
Materials	stainless steel+Aluminum+transparent tempered glass
Diffuser	





DIMENSIONS



Product

Name	12W LED floodlight
Reference	128040K65
Color	Sand Black/Sand Silver
RAL	As per request
Category	floodlight

Light Source

Type	LED
Gross luminous flux	1200 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	12W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	30°/45°/60°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	12W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	
Weight	
Units per package	1
Materials	Die cast aluminum+transparent tempered glass
Diffuser	





Product

Name	7W LED plug-in spotlight
Reference	78040K65
Color	Sand Black/Sand Silver
RAL	As per request
Category	spotlight

Light Source

Type	LED
Gross luminous flux	700 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	7W
Current	350 mA
Efficacy	100lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/38°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	7W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II


OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø40xL170mm
Weight	
Units per package	1
Materials	Die cast aluminum+transparent tempered glass
Diffuser	





DIMENSIONS



Product

Name	7W LED plug-in spotlight
Reference	78040K65
Color	Sand Black/Sand Silver
RAL	As per request
Category	spotlight

Light Source

Type	LED
Gross luminous flux	700 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	7W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	25°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	7W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	
Weight	
Units per package	1
Materials	Die cast aluminum+transparent tempered glass
Diffuser	





Product

Name	6W LED plug-in spotlight
Reference	78040K66
Color	Sand Black/Sand Silver
RAL	As per request
Category	spotlight

Light Source

Type	LED
Gross luminous flux	400 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	7W
Current	350 mA
Efficacy	60lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/38°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	6W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP66
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø40xL170mm
Weight	
Units per package	1
Materials	Die cast aluminum+transparent tempered glass
Diffuser	





Product

Name	6W LED pillar guard light
Reference	58040K65
Color	Sand Black/Sand Silver
RAL	As per request
Category	Pillar light

Light Source

Type	LED
Gross luminous flux	680 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	5W
Current	350 mA
Efficacy	115 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	60°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	5W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	W100*D50*H700mm
Weight	
Units per package	1
Materials	Aluminum+PC lens
Diffuser	





Product

Name	2*4W LED up/down wall light
Reference	49040K65
Color	Grey
RAL	As per request
Category	wall light

Light Source

Type	LED
Gross luminous flux	400 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	8W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	24°/36°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	8W
Voltage	AC220-240V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP65
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø90*W120*H250mm
Weight	
Units per package	1
Materials	Aluminum+transparent tempered glass
Diffuser	





Product

Name	0.5W LED small buried light
Reference	0.58040K65
Color	Brushed stainless steel
RAL	As per request
Category	buried light

Light Source

Type	LED
Gross luminous flux	50 lm
Color temperature	4000K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>80
Power	0.5W
Current	350 mA
Efficacy	100 lm/W
LED lifespan	L70 >50.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	95%
Light beam angle	30°/45°/60°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included – Connected
Power values of the system	0.5W
Voltage	DC24V
Frequency	50/60 Hz
Electrical insulation class	Class II

OTHER DATA

Sealing	IP68
Dimming / Emergency Kits	Optional
Impact resistance	IK06
Recess measurements	Ø42*H74mm
Weight	
Units per package	1
Materials	stainless steel+transparent tempered glass
Diffuser	

